



KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7TH Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,
Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277
uday.sawant@kei-ind.com / swapnil.kanekar@kei-ind.com



PRICE LIST : 1st APRIL 2021

LP NO. KEI/W&F/LP/20-21/13 DT.01.04.2021

INDUSTRIAL MULTI STRAND CABLES

HSN CODE : 85.44.60.20

KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	880	28	1760	12	9.78
0.75	24/0.20	7	1190	28	2380	12	13.22
1.00	32/0.20	11	1530	24	3060	12	17.00
1.50	30/0.25	14	2285	16	4570	8	25.39
2.50	50/0.25	19	3650	12	7300	6	40.56
4.00	56/0.30	26	5395	8	10790	4	59.94
6.00	84/0.30	31	8180	6	16360	3	90.89
10.00	80/0.40	42	14520	1			161.33
16.00	126/0.40	57	22630	1			251.44

KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	960	28	1920	12	10.67
0.75	24/0.20	7	1220	28	2440	12	13.56
1.00	32/0.20	11	1595	24	3190	12	17.72
1.50	30/0.25	14	2385	16	4770	8	26.50
2.50	50/0.25	19	3835	12	7670	6	42.61
4.00	56/0.30	26	5650	8	11300	4	62.78
6.00	84/0.30	31	8510	6	17020	3	94.56
10.00	80/0.40	42	15280	1			169.78
16.00	126/0.40	57	23860	1			265.11

KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	7	1290	28	2580	12	14.33
1.00	32/0.20	11	1705	24	3410	12	18.94
1.50	30/0.25	14	2495	16	4990	8	27.72
2.50	50/0.25	19	3955	12	7910	6	43.94
4.00	56/0.30	26	5745	8	11490	4	63.83
6.00	84/0.30	31	8690	6	17380	3	96.56
10.00	80/0.40	42	15630	1			173.67
16.00	126/0.40	57	24290	1			269.89

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.


PRICE LIST : 1st April 2021
LP NO. KEI/W&F/LP/20-21/13 DT.01.04.2021
PVC INSULATED INDUSTRIAL FLEXIBLE SINGLE & MULTI CORE CABLES
HSN CODE : 85.44.60.20
KEI FLEXIBLE FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

(Rate in Rs. Per 100 Mtrs)

SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	STD. PACK OF 100 MTR COIL	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH	SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH
0.5	16/0.20	4	24	980	1035	1060	35	276/0.4	110	55570	57430	58270
0.75	24/0.20	7	24	1320	1350	1355	50	396/0.4	145	80840	82030	82730
1.0	32/0.20	12	20	1700	1770	1770	70	354/0.5	200	113290	114930	115790
1.5	30/0.25	16	16	2540	2630	2650	95	484/0.5	235	149220	152250	153380
2.5	50/0.25	22	12	4055	4245	4260	120	608/0.5	270	190830	194200	196740
4.0	56/0.30	29	8	5995	6225	6280	150	750/0.5	310	239130	243430	245250
6	84/0.30	37	4	9090	9475	9455	185	925/0.5	360	289830	295550	298020
10	80/0.40	51	1	16130	16740	16980	240	1210/0.5	425	382580	389780	393620
16	126/0.40	68	1	25140	26370	26510	300	1527/0.5	490	476820	485440	490600
25	196/0.40	86	1	39780	41140	41730	400	2036/0.5	590	631220	633160	638920

KEI FLEXIBLE PVC INSULATED MULTICORE FR PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.5	16/0.20	2960	3900	4840	6580	7620	8320	12900	14910	17010	19410	22410	28660
0.75	24/0.20	4000	5110	6580	9080	10360	11430	17390	20190	23320	26580	30860	39420
1.0	32/0.20	4410	6040	7920	10580	12550	14100	21350	24690	28520	32550	37720	48100
1.5	30/0.25	6040	8420	10880	14770	17290	19380	28830	33910	39280	44850	52120	66690
2.5	50/0.25	9790	13540	17750	23410	27680	30900	45650	54050	63190	71770	84020	107270
4.0	56/0.3	15240	22040	28370	38430	44010	50990	75020	88950	103170	117390	137870	177170
6	84/0.3	22460	31930	42570	55320								
10	80/0.4	37550	53900	71120	93670								
16	126/0.4	57830	82840	109360									
25	196/0.4		133990	175870									
35	276/0.4		186310	242960									
50	396/0.4		266810	348780									
70	354/0.5		368170	484450									
95	484/0.5		0	640980									
120	608/0.5												

Note :
KEI 3 CORE FLAT CABLES FOR SUBMERSIBLE PUMP MOTORS

(Rate in Rs. Per 100 Mtrs)

SQ. MM	COND. CONST. (NO./DIA.MM)	RATE
1.5	30/0.25	8960
2.5	50/0.25	13860
4	56/0.3	20890
6	84/0.3	31250
10	80/0.4	51630
16	126/0.4	81570
25	196/0.4	123200

- FRLS Loading - 3% Extra for Multi Core Flexible Cables.**
- KEI 3 Core Flat Submersible Cables PVC Insulated & Sheathed with XLPE can be supplied at the same rates as PVC insulated cables.
- Packing for 3 Core Flat Submersible Cables :**
 - Cables upto 4sqmm are supplied in 500Mtr/1000Mtr drums.
 - Cables from 6sqmm to 25sqmm are supplied in 500Mtr drums.
 - Cables of 1.5sqmm, 2.5sqmm & 4sqmm are also supplied in 300Mtr coil.
- Packing for Single & Multi Core Round Wire Flexible cables :**
 - Single Core Flexible cables upto 6sqmm are supplied in Master Carton as shown above.
 - Single Core 10sqmm and above will be supplied in single coil packing.
 - Single Core 120sqmm and above & Multicore 6sqmm & above available in coil packing.

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- This Price List is subject to change without prior notice.