



KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7th Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,
Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277

spa.mumbai@kei-ind.com



PRICE LIST : 8th MARCH 2022

LP NO. KEI/W&F/LP/21-22/08 DT.08.03.2022

INDUSTRIAL MULTI STRAND CABLES

HSN CODE : 85.44.60.20

KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	1050	28	2100	12	11.67
0.75	24/0.20	7	1410	28	2820	12	15.67
1.00	32/0.20	11	1850	24	3700	12	20.56
1.50	30/0.25	14	2710	16	5420	8	30.11
2.50	50/0.25	19	4350	12	8700	6	48.33
4.00	56/0.30	26	6430	8	12860	4	71.44
6.00	84/0.30	31	9750	6	19500	3	108.33
10.00	80/0.40	42	17370	1			193.00
16.00	126/0.40	57	27060	1			300.67

KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	1140	28	2280	12	12.67
0.75	24/0.20	7	1450	28	2900	12	16.11
1.00	32/0.20	11	1940	24	3880	12	21.56
1.50	30/0.25	14	2830	16	5660	8	31.44
2.50	50/0.25	19	4560	12	9120	6	50.67
4.00	56/0.30	26	6740	8	13480	4	74.89
6.00	84/0.30	31	10200	6	20400	3	113.33
10.00	80/0.40	42	18180	1			202.00
16.00	126/0.40	57	28400	1			315.56

KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	7	1530	28	3060	12	17.00
1.00	32/0.20	11	2070	24	4140	12	23.00
1.50	30/0.25	14	2970	16	5940	8	33.00
2.50	50/0.25	19	4710	12	9420	6	52.33
4.00	56/0.30	26	6840	8	13680	4	76.00
6.00	84/0.30	31	10340	6	20680	3	114.89
10.00	80/0.40	42	18600	1			206.67
16.00	126/0.40	57	28900	1			321.11

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.



KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7th Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,
Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277
spa.mumbai@kei-ind.com



PRICE LIST : 8th MARCH 2022

LP NO. KEI/W&F/LP/21-22/08 DT.08.03.2022

PVC INSULATED INDUSTRIAL FLEXIBLE SINGLE & MULTI CORE CABLES

HSN CODE : 85.44.60.20

KEI FLEXIBLE FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

(Rate in Rs. Per 100 Mtrs)

SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	STD. PACK OF 100 MTR COIL	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH	SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH
0.5	16/0.20	4	24	1160	1250	1260	35	276/0.4	110	66450	68660	69680
0.75	24/0.20	7	24	1565	1600	1610	50	396/0.4	145	96670	98090	98920
1.0	32/0.20	12	20	2055	2140	2155	70	354/0.5	200	135470	137430	138460
1.5	30/0.25	16	16	3010	3140	3145	95	484/0.5	235	178430	182050	183400
2.5	50/0.25	22	12	4835	5050	5065	120	608/0.5	270	228180	232210	235250
4.0	56/0.30	29	8	7145	7440	7490	150	750/0.5	310	285940	291080	293260
6	84/0.30	37	4	10835	11280	11335	185	925/0.5	360	346550	353410	356360
10	80/0.40	51	1	19300	20010	20200	240	1210/0.5	425	457460	466060	470680
16	126/0.40	68	1	30070	31530	31560	300	1527/0.5	490	570150	580460	586640
25	196/0.40	86	1	47570	49180	49890	400	2036/0.5	590	754770	757090	763980

KEI FLEXIBLE PVC INSULATED MULTICORE FR PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.5	16/0.20	3540	4680	5820	7910	9160	9990	15510	17910	20420	23310	26920	34440
0.75	24/0.20	4810	6140	7910	10910	12440	13740	20890	24270	28030	31930	37080	47370
1.0	32/0.20	5360	7310	9610	12700	15090	16930	25660	29660	34280	39110	45320	57780
1.5	30/0.25	7310	10210	13190	17740	20780	23290	34630	40750	47190	53890	62610	80130
2.5	50/0.25	11860	16430	21530	28130	33250	37130	54850	64930	75940	86230	100950	128890
4.0	56/0.3	18480	26730	34390	46150	52880	61260	90150	106880	123970	141050	165650	212880
6	84/0.3	27230	38720	51630	66470								
10	80/0.4	45540	65350	86240	112540								
16	126/0.4	70130	100470	132610									
25	196/0.4		161700	212250									
35	276/0.4		224850	293220									
50	396/0.4		322000	420930									
70	354/0.5		444330	584660									
95	484/0.5		0	773580									
120	608/0.5												

Note :

KEI 3 CORE FLAT CABLES FOR SUBMERSIBLE PUMP MOTORS

(Rate in Rs. Per 100 Mtrs)

SQ. MM	COND. CONST. (NO./DIA.MM)	RATE
1.5	30/0.25	10500
2.5	50/0.25	16240
4	56/0.3	24490
6	84/0.3	36640
10	80/0.4	60520
16	126/0.4	95640
25	196/0.4	143750

- FRLS Loading - 3% Extra for Multi Core Flexible Cables.**
- KEI 3 Core Flat Submersible Cables PVC Insulated & Sheathed with XLPE can be supplied at the same rates as PVC insulated cables.
- Packing for 3 Core Flat Submersible Cables :**
 - Cables upto 4sqmm are supplied in 500Mtr/1000Mtr drums.
 - Cables from 6sqmm to 25sqmm are supplied in 500Mtr drums.
 - Cables of 1.5sqmm, 2.5sqmm & 4sqmm are also supplied in 300Mtr coil.
- Packing for Single & Multi Core Round Wire Flexible cables :**
 - Single Core Flexible cables upto 6sqmm are supplied in Master Carton as shown above.
 - Single Core 10sqmm and above will be supplied in single coil packing.
 - Single Core 120sqmm and above & Multicore 6sqmm & above available in coil packing.

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- This Price List is subject to change without prior notice.