


PRICE LIST : 21ST MAY 2022
LP NO. KEI/W&F/LP/22-23/02 DT.21.05.2022
INDUSTRIAL MULTI STRAND CABLES
HSN CODE : 85.44.60.20
KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	1000	28	2000	12	11.11
0.75	24/0.20	7	1340	28	2680	12	14.89
1.00	32/0.20	11	1760	24	3520	12	19.56
1.50	30/0.25	14	2580	16	5160	8	28.67
2.50	50/0.25	19	4140	12	8280	6	46.00
4.00	56/0.30	26	6120	8	12240	4	68.00
6.00	84/0.30	31	9280	6	18560	3	103.11
10.00	80/0.40	42	16530	1			183.67
16.00	126/0.40	57	25750	1			286.11

KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	1090	28	2180	12	12.11
0.75	24/0.20	7	1380	28	2760	12	15.33
1.00	32/0.20	11	1840	24	3680	12	20.44
1.50	30/0.25	14	2700	16	5400	8	30.00
2.50	50/0.25	19	4340	12	8680	6	48.22
4.00	56/0.30	26	6410	8	12820	4	71.22
6.00	84/0.30	31	9710	6	19420	3	107.89
10.00	80/0.40	42	17300	1			192.22
16.00	126/0.40	57	27030	1			300.33

KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	7	1460	28	2920	12	16.22
1.00	32/0.20	11	1970	24	3940	12	21.89
1.50	30/0.25	14	2820	16	5640	8	31.33
2.50	50/0.25	19	4480	12	8960	6	49.78
4.00	56/0.30	26	6510	8	13020	4	72.33
6.00	84/0.30	31	9840	6	19680	3	109.33
10.00	80/0.40	42	17710	1			196.78
16.00	126/0.40	57	27510	1			305.67

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.


PRICE LIST : 21st MAY 2022
LP NO. KEI/W&F/LP/22-23/02 DT.21.05.2022
PVC INSULATED INDUSTRIAL FLEXIBLE SINGLE & MULTI CORE CABLES
HSN CODE : 85.44.60.20
KEI FLEXIBLE FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

(Rate in Rs. Per 100 Mtrs)

SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	STD. PACK OF 100 MTR COIL	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH	SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH
0.5	16/0.20	4	24	1110	1190	1200	35	276/0.4	110	63250	65350	66320
0.75	24/0.20	7	24	1490	1520	1535	50	396/0.4	145	92010	93360	94160
1.0	32/0.20	12	20	1955	2040	2045	70	354/0.5	200	128940	130810	131790
1.5	30/0.25	16	16	2865	2990	3000	95	484/0.5	235	169830	173280	174570
2.5	50/0.25	22	12	4600	4800	4820	120	608/0.5	270	217190	221030	223920
4.0	56/0.30	29	8	6800	7080	7120	150	750/0.5	310	272170	277060	279140
6	84/0.30	37	4	10310	10740	10790	185	925/0.5	360	329860	336390	339200
10	80/0.40	51	1	18370	19050	19220	240	1210/0.5	425	435430	443620	448010
16	126/0.40	68	1	28610	30010	30030	300	1527/0.5	490	542690	552500	558380
25	196/0.40	86	1	45270	46810	47490	400	2036/0.5	590	718420	720630	727190

KEI FLEXIBLE PVC INSULATED MULTICORE FR PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.5	16/0.20	3370	4450	5540	7530	8720	9510	14760	17050	19440	22190	25630	32780
0.75	24/0.20	4580	5840	7530	10380	11840	13080	19880	23100	26680	30390	35290	45090
1.0	32/0.20	5100	6960	9150	12090	14360	16120	24420	28240	32630	37230	43140	55000
1.5	30/0.25	6960	9720	12560	16880	19770	22170	32960	38780	44920	51290	59600	76270
2.5	50/0.25	11280	15640	20490	26770	31650	35340	52210	61800	72280	82080	96090	122690
4.0	56/0.3	17590	25440	32740	43930	50330	58310	85800	101740	118000	134250	157680	202630
6	84/0.3	25920	36850	49150	63260								
10	80/0.4	43340	62210	82090	107120								
16	126/0.4	66750	95630	126230									
25	196/0.4		153910	202030									
35	276/0.4		214020	279100									
50	396/0.4		306490	400660									
70	354/0.5		422930	556500									
95	484/0.5		0	736320									
120	608/0.5												

Note :
KEI 3 CORE FLAT CABLES FOR SUBMERSIBLE PUMP MOTORS

(Rate in Rs. Per 100 Mtrs)

SQ. MM	COND. CONST. (NO./DIA.MM)	RATE
1.5	30/0.25	9990
2.5	50/0.25	15460
4	56/0.3	22980
6	84/0.3	34220
10	80/0.4	57610
16	126/0.4	91030
25	196/0.4	136820

- FRLS Loading - 3% Extra for Multi Core Flexible Cables.**
- KEI 3 Core Flat Submersible Cables PVC Insulated & Sheathed with XLPE can be supplied at the same rates as PVC insulated cables.
- Packing for 3 Core Flat Submersible Cables :**
 - Cables upto 4sqmm are supplied in 500Mtr/1000Mtr drums.
 - Cables from 6sqmm to 25sqmm are supplied in 500Mtr drums.
 - Cables of 1.5sqmm, 2.5sqmm & 4sqmm are also supplied in 300Mtr coil.
- Packing for Single & Multi Core Round Wire Flexible cables :**
 - Single Core Flexible cables upto 6sqmm are supplied in Master Carton as shown above.
 - Single Core 10sqmm and above will be supplied in single coil packing.
 - Single Core 120sqmm and above & Multicore 6sqmm & above available in coil packing.

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- This Price List is subject to change without prior notice.